

TOPCLEAN 5L

DESCRIPTION

- Professional alkaline multipurpose cleaner and degreaser
- Ideal for removing ink stains, grease, oil, nicotine traces, food residues etc.
- Can also be used in mechanical workshops, for cleaning engines and greasy parts, garage floors, cleaning bodywork before painting.
- Also suitable for cleaning windows, glass, mirrors and PVC.
- Applicable to domestic and professional use for cleaning walls, floors, woodwork ...
- Removes soot stains on glass after a fire.
- Non-toxic
- Non-flammable
- Biodegradable
- If dosed, harmless to the skin
- Double action when using hot water at 50°C

• Appearance	vloeibare bereiding
• Odor	kenmerk
• Viscosity mPa.s/20°C	1
• Vapor pressure/20°C Pa	2332
• Relative density /20°C	1,005
• PH	12,9
• Spontaneous combustion °C	230
• Flash point °C	/
• Boiling point / path °C	100 - 173
• Melting point / range °C	0
• Solubility in water	volledig oplosbaar



APPLICATION – DOSE

- Manual use:
 - Dilute 2.5% TOPCLEAN in water.
 - Use with a sponge or brush.
 - Rinse well.
- Spray:
 - Dilute 5 to 10% TOPCLEAN in water.
 - Spray from bottom to top.
 - Allow to work for max. 2 minutes and rinse thoroughly with water.
- High pressure use:
 - Add 0.5 to 2% of TOPCLEAN to water at a temperature of 50°C.
 - Leave to act for max. 2 minutes and rinse thoroughly with high pressure.

STORAGE

- Store in a well closed package, in a closed, frost-free and well ventilated place.
- Avoid metal packaging.
- Treat with caution to avoid spillage.