

KEMTEX

M-FLEX NITRIL FOAM

Technical data sheet

REF. 11.44N043-9

11.44N043-10

11.44N043-11

CHARACTERISTICS

- super light nitrile foam coating offers a high degree of dexterity and flexibility
- non-slip; the coating provides a good grip on dry, greasy and oily objects
- breathable coating keeps hands dry and cool
- dark colour makes the glove ideal for use in environments with a certain level of contamination, such as garages and workshops
- Colour: grey/black
- Size: 9 to 11
- 144 pairs



APPLICATIONS

The gloves are ideal for construction, industry, maintenance, transport, installation technology, assembly work, automotive industry and general assembly.

EN 420		EN 388	
Algemene eisen			
		4131 ABCD	
		A Abrasie (0-4) B Snijweerstand (0-5) C Scheurweerstand (0-4) D Perforatie (0-4)	

The manufacturer, or his authorised representative established within the Community, declares that the Personal Protective Equipment (PPE) described here is in conformity with the provisions of Directive 89/686/EEC and with the European harmonised standards EN420:2003+A1:2009 and EN388:2003 and is identical to the PPE covered by the EC type-examination certificate No 03112319 issued by: Centexbel (0493), Technologiepark 7, B-9052 Zwijnaarde, Belgium

And has been subject to the procedure referred to in Article 11, point B of Directive 89/686/EEC under the supervision of the notified body Centexbel (0493), Technologiepark 7, B-9052 Zwijnaarde, Belgium

KEMTEX.BE

HCT NV
Europalaan 24b
9800 Deinze
Belgium (Europe)
T +32 (0)9 380 45 43
mail@kemtex.be



www.kemtex.be



@kemtexofficial



@kemtex_official