

PROFESSIONAL ECRU MASKING TAPE

DESCRIPTION

Universal utility grade professional automotive masking tape with FSC® certified crepe paper backing and solvent-based adhesive designed for any type of paint and applications with temperature drying cycles of up to 80°C (30 min.). Offers high adaptability to irregular surfaces and assures clean edges. It performs in overlapping the tape, with masking paper and masking film with good holding power. Easy and clean removal without leaving adhesive residue on the application surface.

TECHNICAL DATA

- Total weight: 90 g/m²
- Total thickness: 120 µm
- MD tensile strength : 95 N/25 mm.
- MD elongation at break: 7 %
- Adhesion to steel plate : 5.25 N/25 mm.
- Service temperature : 80°C for 30 minutes
- Backing material : Saturated crepe paper
- Type of adhesive : Natural rubber
- Color: ecru 



ART. N°	WIDTH/MM.	LENGHT/M.	#ROLLS/BOX
12.3012-18	18	45	48
12.3012-24	24	45	36
12.3012-36	36	45	24
12.3012-48	48	45	18

STORAGE AND SHELF LIFE

Suggested storage in dry area away from direct sunlight temperature should range from 15°C to 25°C with max relative humidity of 50%.

Shelf life : 12 months.

KEMTEX.BE

HCT NV
Europalaan 24b
9800 Deinze
Belgium (Europe)
T +32 (0)9 380 45 43
mail@kemtex.be



www.kemtex.be



@kemtexofficial



@kemtex_official