

SANDING BLOCK

DESCRIPTION

Fine carbon sanding blocks for fast and professional paint correction

- The safest and most durable way to eliminate any type of paint defects
- Designed to remove paint imperfections from fresh paint s.a. runners, orange peel, dust inclusion, fish eyes
- Can be used over and over again - economical in use
- Will not swell
- Keep their shape
- Do not disintegrate
- Available separate in 4 different grits or in set

TECHNICAL

- Consists of a porous carbon compression with calibrated abrasive particles.
- Size: l: 60 mm x w: 20 mm x h: 30 mm
- Available grits:
 - P 800 - GREY Ref. 14.72020-01
 - P 1500 - YELLOW Ref. 14.72020-02
 - P 2000 - GREEN Ref. 14.72020-03
 - P 3000 - RED Ref. 14.72020-04
 - Set of 4 grits Ref. 14.72020-SET

INSTRUCTIONS FOR USE



Always dry paint IR and allow to cool before processing.
FOR WET USE ONLY

- First use: keep carbon blocks submerged in water for 24 hours, so to be completely soaked in water and get down to the bottom of the container.
- 1. Choose the block grit according to the kind of application , work from coarse (P800) up to fine (P3000)
- 2. Slightly round off the corners on some P400 waterproof sand paper
- 3. Wet the surface to be treated and move the block keeping it parallel to the working area.
- Protect the paint with the KEMTEX CORRECT - SHEET
- 4. Always work using water.
- 5. End the work always using the P3000 bar, after also rounding off the corners.
- 6. Wipe off and polish as usual.



Always store the block in a closed container filled with clean water.