

DESCRIPTION

- Specially designed for cleaning painting equipment.
- Complex composition of powerful, fast-drying solvents.
- Translucent liquid with characteristic odour and high solvent content.
- Boiling temperature: 110 °C to 130 °C.

USAGE

- Cleaner for materials contaminated by all types of paint.
- Do not allow prolonged contact with seals of spray guns.
- Do not use as paint thinner.
- Can be used as a degreaser, depending on the surface.
- Very fast degreaser for metal surfaces.

USER MANUAL

- Use by brushing, wiping or dipping.
- Composition according to Regulation 648/2004

Nom INCI / IUCPA	%	N° CAS
TOLUENE	25-50	108-88-3
PROPANONE	25-50	67-64-1
ACETATE D'ETHYLE	10-15	141-78-6
ACETATE DE N-BUTYLE	10-15	123-86-4
ACETATE D'ISOPROPYLE	10-15	108-21-4
METHYLETHYLCETONE	5-10	78-93-3
METHYL ISOBUTYL CETONE	5-10	108-10-1
ETHYL ALCOHOL	1-5	64-17-5
ISOPROPYL ALCOHOL	1-5	67-63-0
XYLENE	1-5	1330-20-7
ETHYLBENZENE	0,1-0,5	100-41-4



CONTENTS

15.11801-5	5 LTR
15.11801-30	20 LTR

HYGIENE AND SAFETY

- Slightly flammable product, ensure proper industrial safety and personal protection.
- See Safety Data Sheet for further information.