

KEM-STRIPPER LIQUID SAFE

DESCRIPTION

- KEM-STRIPPER LIQUID SAFE removes water-based and polyurethane paint layers.
- Suitable for stripping floors and gratings.
- Also suitable for stripping varnishes and stains.
- Dry residue stripping principle.
- Effective on wood, stone, concrete, steel, stainless steel, aluminum.
- Appearance: colorless to slightly yellow liquid
- PH: acid
- Density: 0.85
- VOC content: 760 g/l (2004/42/CE - II B (a) preparatory products: 850g/l max.)
- Flash point: < 21°C
- This methylene chloride free paint stripper complies with the Commission Regulation n° 276/2010 of 31/03/2010*.

USE

- KEM-STRIPPER LIQUID SAFE is used pure, by dipping or by spreading and at room temperature.
- Stripping time depends on the thickness and nature of the paint to be removed.
- Average time of action: 5 to 15 minutes.
- ATTENTION: After removal of the paint layers, the stripped surfaces may remain slightly slippery. Rinse with water if necessary.
- IMPERATIVE: Do not introduce water into the bath
- Work in a ventilated room.
- In the cabin and the laboratory, use ventilation.
- Wear gloves and goggles.
- Acid product, be careful with sensitive surfaces.
- For further information, consult the safety data sheet.

